

Accessories

» Solis Data Logging Stick



Data Logging Stick
S3-GPRS-ST



Data Logging Stick
S3-WIFI-ST

GPRS/WIFI Data Logging Stick

- Plug and play, quick installation
- Fault alarm, real-time monitoring
- Plug and play, convenient and fast
- Status indicator, easy to display working status
- RESET button, one key to send data, convenient debugging

Datasheet

Model Name	S3-GPRS-ST	S3-WIFI-ST
------------	------------	------------

Communication

Supported device type	Solis inverter	
Max. number of connected devices	1	≤10
Data collection intervals	5 minutes (adjustable: 1-15 minutes)	
Status indicator	3 LEDs	
Communication interface	4 Pin	
Communication rate	Max. rate: 85.6Kbps	Max. rate: 72Mbps
Wireless working frequency	850/900/1800/1900 MHz	2.4 GHz
Operator	Support mobile 2G	/
Configuration method	APP/WEB	
Data storage space	4 MB FLASH	8 MB FLASH

Electrical

Input voltage	DC 5V(+/-5%)
Working current	150 mA~2100 mA
Static power consumption	<2 W
Power consumption	<5 W

Environment

Operating temperature	-30 ~ +65°C
Relative humidity	5%~95%, non-condensing
Storage temperature	-40 ~ +70°C
Storage humidity	< 40%
Operating altitude	4000 m
Protection degree	IP65

Mechanical

Dimensions (L*W*H)	130*45*45 mm
Installation method	Insert+Screw
Weight	61 g

Other

Certificates	CE, FCC
--------------	---------